

TEMY PRO 12-18-30 KW



A COMPACT SIZE KITCHEN-BOILER WITH
FLUE-GAS EXIT ON TOP (OR Laterally)

Boiler chamber is entirely made of steel, while the frame parts of the upper plate are made of stainless steel AISI 314. The door frames are made of cast-iron. The upper door is filled with fireproof glass, while the lower door is made of steel.



Type	TEMY PRO 12	TEMY PRO 18	TEMY PRO 30
Nominal power	12 KW	18 KW	30 KW
Power transmitted to the central heating	9 KW	13 KW	25 KW
Temperature range	60-80°C	60-80°C	60-80°C
Power range (min-max)	4-12 KW	6-18 KW	10-30 KW
Minimum temperature of the return line	60°C	60°C	60°C
Width (B)	710 mm	710 mm	710 mm
Height (H)	810 mm	960 mm	910 mm
Length (L)	700 mm	770 mm	800 mm
Total weight of the boiler	191 kg	218 kg	238 kg
Flow / Return (F) (inch)	1"	1"	1"
Fill / Drain tap (inch)	1/2"	1/2"	1/2"
Flue gas diameter (E)	Ø 118 mm	Ø 128 mm	Ø 148 mm
Necessary draught	13 Pa	14 Pa	15 Pa
Max working pressure	2,5 bar	2,5 bar	2,5 bar
Boiler water volume	31 lit	40 lit	65 lit
Upper door size	258 x 196 mm	258 x 196 mm	258 x 196 mm
Lower door size	258 x 196 mm	258 x 196 mm	258 x 196 mm